



PRODUCT DATA SHEET
CLASSIC 4/5

SPENDOR

MADE FOR MUSIC. DESIGNED FOR YOU.

The Spendor Classic 4/5 loudspeaker is the most charming and beautifully balanced sounding small Spendor Classic ever. A very compact shelf or stand mount, the Classic 4/5 is a multi-talented loudspeaker, it delivers low frequencies with a remarkable sense of depth and extension and is notably free from the artificial brightness and over-blown bass which characterises the sound of most modern speakers.

HIGHLIGHTS

- The Spendor Classic 4/5 mirrors the elegant timeless style and finish of the latest generation Spendor Classic loudspeakers, as well as maintaining the captivating warmth, natural clarity, and sonics precision of its distinguished predecessors.
- Spendor's proprietary 15cm EP77 polymer bass/mid cone produces a natural sound that is free from colouration whilst delivering room friendly bass that is taut and controlled.
- 310mm tall and with a depth of only 170mm the Classic 4/5 closed box design can be positioned in any small space or on the dedicated Spendor Classic Stand, which offers the best results.
- Available in two luxurious real wood veneer finishes – walnut and cherry.
- Designed and Manufactured in the UK.

TECHNICAL SPECIFICATION

Description	2-way stand or shelf mount loudspeaker
Enclosure type	Sealed enclosure
Input connection	One pair gold-plated precision binding posts
Typical in-room response	55Hz – 25kHz
Power handling	100 watts unclipped programme
Amplifier	25-100 watts
Sensitivity	84dB for 1 watt at 1 metre
Nominal impedance	8 ohms (min 6.6)
HF driver	22mm polyamide dome
Bass/mid driver	15cm EP77 polymer cone
Crossover frequency	4.2 kHz
Net Weight	5kg
Height	308mm
Width	188mm
Depth	165mm
Finishes	Cherry, Walnut
Included	Magnetic grille, small polymer feet
Recommended stand	Dedicated Spendor Classic 4/5 Stand (not supplied)



Cherry



Walnut

SPENDOR

Spendor Audio Systems Ltd, G5 Ropemaker Park, South Road, Hailsham, East Sussex BN27 3GY UK
+44 (0)1323 843474 info@spendoraudio.com spendoraudio.com